

ZIPLink Connection Cables			
Part Number	Description	Insulation Rating	Price
<b>CLICK ZIPLink Cables</b>			
<b>ZL-C0-CBL11</b>	Cable for module with 11 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-C0-CBL11-1</b>	Cable for module with 11 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-C0-CBL11-2</b>	Cable for module with 11 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-C0-CBL20</b>	Cable for module with 20 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-C0-CBL20-1</b>	Cable for module with 20 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-C0-CBL20-2</b>	Cable for module with 20 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>DL05 and DL06 ZIPLink Cables</b>			
<b>ZL-D0-CBL8</b>	Cable for module with 8 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-D0-CBL8-1</b>	Cable for module with 8 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D0-CBL8-2</b>	Cable for module with 8 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D0-CBL10</b>	Cable for module with 10 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-D0-CBL10-1</b>	Cable for module with 10 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D0-CBL10-2</b>	Cable for module with 10 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D0-CBL13</b>	Cable for module with 13 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-D0-CBL13-1</b>	Cable for module with 13 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D0-CBL13-2</b>	Cable for module with 13 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D0-CBL24</b>	Cable for module with 24-pin connector to 24-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-D0-CBL24-1</b>	Cable for module with 24-pin connector to 24-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D0-CBL24-2</b>	Cable for module with 24-pin connector to 24-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D0-CBL24-L</b>	Cable for module with 24-pin connector to 24-pin connector for LED module, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-D0-CBL24-1L</b>	Cable for module with 24-pin connector to 24-pin connector for LED module, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D0-CBL24-2L</b>	Cable for module with 24-pin connector to 24-pin connector for LED module, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D0-CBL24-1P</b>	Cable for module with 24-pin connector to 24-wire pigtail, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D0-CBL24-2P</b>	Cable for module with 24-pin connector to 24-wire pigtail, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>DL205 ZIPLink Cables</b>			
<b>ZL-D2-CBL10</b>	Cable for module with 10 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-D2-CBL10-1</b>	Cable for module with 10 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D2-CBL10-2</b>	Cable for module with 10 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D2-CBL19</b>	Cable for module with 19 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-D2-CBL19-1</b>	Cable for module with 19 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D2-CBL19-2</b>	Cable for module with 19 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40</b>	Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-1</b>	Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-2</b>	Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-X</b>	Cable w/105° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-1X</b>	Cable w/105° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-2X</b>	Cable w/105° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-1P</b>	Cable w/180° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-2P</b>	Cable w/180° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-1XP</b>	Cable w/105° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-2XP</b>	Cable w/105° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D24-CON-R</b>	ZIPLink ribbon-style connector, 40-pin, qty. 2	N/A	<--->
<b>ZL-D24-CON</b>	ZIPLink solder-style connector, 180°, 40-pin, qty. 2	N/A	<--->
<b>ZL-D24-CON-X</b>	ZIPLink solder-style connector, 105°, 40-pin, qty. 2	N/A	<--->



ZL-C0-CBL11



ZL-D0-CBL10-1



ZL-D0-CBL24-1



ZL-D2-CBL10



ZL-D24-CBL40



ZL-D24-CBL40-1P

ZIPLink Connection Cables			
Part Number	Description	Insulation Rating	Price
<b>DL305 ZIPLink Cables</b>			
<b>ZL-D3-CBL18</b>	Cable for module with 18 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-D3-CBL18-1</b>	Cable for module with 18 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D3-CBL18-2</b>	Cable for module with 18 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>DL405 ZIPLink Cables</b>			
<b>ZL-D4-CBL20</b>	Cable for module with 20 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-D4-CBL20-1</b>	Cable for module with 20 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D4-CBL20-2</b>	Cable for module with 20 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40</b>	Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-1</b>	Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-2</b>	Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-X</b>	Cable w/45° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-1X</b>	Cable w/45° plug for module with 40-pin connector to 40-pin connector, 24 AWG 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-2X</b>	Cable w/45° plug for module with 40-pin connector to 40-pin connector, 24 AWG 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-1P</b>	Cable w/180° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-2P</b>	Cable w/180° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-1XP</b>	Cable w/45° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-D24-CBL40-2XP</b>	Cable w/45° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-D24-CON-R</b>	ZIPLink ribbon-style connector, 40-pin, qty. 2	N/A	<--->
<b>ZL-D24-CON</b>	ZIPLink solder-style connector, 105°, 40-pin, qty. 2	N/A	<--->
<b>ZL-D24-CON-X</b>	ZIPLink solder-style connector, 45°, 40-pin, qty. 2	N/A	<--->
<b>Productivity3000 ZIPLink Cables</b>			
<b>ZL-P3-CBL20</b>	Cable for module with 20 terminals to 20-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-P3-CBL20-1</b>	Cable for module with 20 terminals to 20-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-P3-CBL20-2</b>	Cable for module with 20 terminals to 20-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-P3-CBL20-L</b>	Cable for module with 20-pin connector to 20-pin connector for LED module, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-P3-CBL20-1L</b>	Cable for module with 20-pin connector to 20-pin connector for LED module, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-P3-CBL20-2L</b>	Cable for module with 20-pin connector to 20-pin connector for LED module, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-P3-CBL20-P</b>	Cable for module with 20-pin connector to 20-wire pigtail, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-P3-CBL20-1P</b>	Cable for module with 20-pin connector to 20-wire pigtail, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-P3-CBL20-2P</b>	Cable for module with 20-pin connector to 20-wire pigtail, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-CBL40</b>	Cable for module with 40-pin connector to 40-pin connector, 24 AWG, 1.6 ft. (0.5m)	300V, 80°C	<--->
<b>ZL-CBL40-1</b>	Cable for module with 40-pin connector to 40-pin connector, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-CBL40-2</b>	Cable for module with 40-pin connector to 40-pin connector, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->



**ZL-D3-CBL20**



**ZL-D4-CBL20**



**ZL-D24-CBL40**



**ZL-P3-CBL20-1**

ZIPLink Connection Cables			
Part Number	Description	Insulation Rating	Price
<b>Universal ZIPLink Cables</b>			
<b>ZL-CBL24-1P</b>	Cable with 24-pin connector to 24-wire pigtail for connecting any 24-pin ZIPLink module to another device, 24 AWG, 3.3 ft. (1.0m)	300V, 80°C	<--->
<b>ZL-CBL24-2P</b>	Cable with 24-pin connector to 24-wire pigtail for connecting any 24-pin ZIPLink module to another device, 24 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>Serial Communication ZIPLink Cables</b>			
<b>ZL-DB9-CBL-2</b>	Shielded cable with 9-pin D-sub male to female connectors, 28 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-DB15-CBL-2</b>	Shielded cable with 15-pin D-sub male to female connectors, 28 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-DB25-CBL-2</b>	Shielded cable with 25-pin D-sub male to female connectors, 28 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>ZL-RJ12-CBL-2</b>	Crossover cable with 6-pin RJ12 to 6-pin RJ12 connectors, 26 AWG, 6.6 ft. (2.0m)	150V, 60°C	<--->
<b>ZL-RJ12-CBL-2P</b>	Cable with 6-pin RJ12 connector to 6-wire pigtail, 26 AWG, 6.6 ft. (2.0m)	150V, 60°C	<--->
<b>AC Drive and Servo ZIPLink Cables</b>			
<b>GS-RJ12-CBL-2</b>	RS232 cable with 6-pin RJ12 connector to 6-pin RJ12 connector for GS2 Series drives ONLY 26 AWG, 6.6 ft. (2.0m)	300V, 80°C	<--->
<b>GS-485HD15-CBL-2</b>	RS485 shielded twisted pair cable with 6-pin RJ12 to HD 15-pin male connector for all GS Series/DuraPulse drives, 28 AWG, 6.6 ft. (2.0m)	30V, 80°C	<--->
<b>SVC-232RJ12-CBL-2</b>	RS232 shielded twisted pair cable with 6-pin RJ12 to 6-pin IEEE connector for all SureServo amplifiers, 6.6 ft. (2.0m)	30V, 80°C	<--->
<b>SVC-485HD15-CBL-2</b>	RS485 shielded twisted pair cable with HD 15-pin male to 6-pin IEEE connector for all SureServo amplifiers, 6.6 ft. (2.0m)	30V, 80°C	<--->
<b>ZL-SVC-CBL50</b>	Shielded twisted pair cable with 50-pin connectors to connect any SureServo amplifier to a ZL-RTB50 module, 28 AWG, 1.6 ft. (0.5m)	30V, 80°C	<--->
<b>ZL-SVC-CBL50-1</b>	Shielded twisted pair cable with 50-pin connectors to connect any SureServo amplifier to a ZL-RTB50 module, 28 AWG, 3.3 ft. (1.0m)	30V, 80°C	<--->
<b>ZL-SVC-CBL50-2</b>	Shielded twisted pair cable with 50-pin connectors to connect any SureServo amplifier to a ZL-RTB50 module, 28 AWG, 6.6 ft. (2.0m)	30V, 80°C	<--->



**ZL-CBL24-1P**



**ZL-DB9-CBL-2**



**ZL-RJ12-CBL-2**



**GS-RJ12-CBL-2**



**GS-485HD15-CBL-2**



**SVC232RJ12-CBL-2**



**ZL-RJ12-CBL-2P**



**SVC485HD15-CBL-2**



**ZL-SVC-CBL50**